



序号 No.	主要技术参数 Main Technical Specification	型号 Type	
		ZKTJ80/1.14	
电气参数 ELECTRIC RATINGS			
1	额定电压 Rated Voltage	kV	1.14
2	额定电流 Rated Current	A	80
3	额定频率 Rated Frequency	Hz	50/60
4	额定短时（1 分钟）工频耐受电压 Rated Short-time(1min) Power-Frequency Withstand Voltage	kV	10
5	触头自闭力下的回路电阻 Circuit Resistance At Contact Force From Atmosphere	$\mu\Omega$	≤ 150
6	雷电冲击耐受电压 Lightning Impulse Withstand Voltage	kV	18
7	额定关合能力 Rated Making Capacity	kA/50 次 Times	0.8
8	额定开断能力 Rated Breaking Capacity	kA/50 次 Times	0.64
9	极限开断能力 Limited Breaking Capacity	kA/3 次 Times	2
10	额定短时耐受电流，10 秒 Rated Short-time Withstand Current, 10s	kA	0.64
11	额定峰值耐受电流 Rated Peak Withstand Current	kA	1.6
寿命 LIFE			
1	机械寿命 Mechanical Life	次 Times	1,000,000
2	电寿命 Electrical Life	次 Times	60,000
3	储存时间 Storage Life	年 years	≥ 10
4	触头允许磨损厚度 Contacts Erosion Limit	mm	1
机械数据 MECHANICAL DATA			
1	触头自闭力 Contact Force From Atmosphere	N	12 \pm 5
2	触头反力 Counterforce of Contacts at Full Stroke	N	35 \pm 10
配套的真空开关设备应满足的机械参数 MECHANICAL DATA OF VACUUM SWITCH EQUIPPED WITH THE INTERRUPTERS			
1	触头开距 Contact Stroke	mm	1.8 \pm 0.2
2	超行程 Overtrave	mm	1 \pm 0.2
3	平均分闸速度 Average Opening Speed	m/s	0.3~0.5
4	平均合闸速度 Average closing speed	m/s	0.05~0.15
5	触头合闸弹跳时间 Contact Bouncing Duration at Cosing Operation	ms	≤ 3
6	额定触头压力 Rated Added External Contactfinal Force	N	70





ZKTJ80/1.14 (RN3.393.020C)

型接触器用真空灭弧室

Vacuum Interrupter For Contactor

